
NEW

Technical Data // STLZ1550/..F-3.81-V-P2.6-BK-HT

Spacing 3.81 mm

PTR HARTMANN
A Phoenix Mecano Company



Highlights	
2 to 8 poles	
Vertical pin strip	
Spacing 3.81 mm	
With fixing flange	
Reflow soldering	
Automatic assembly (tape-on-reel)	
THR	
Pin length 2.6 mm	
Pin length 1.4 mm | 3.4 mm also available	
Wire Sizes	
Solid min	-
Solid max	-
Stranded (flexible) min	-
Stranded (flexible) max	-
Stranded with ferrule min	-
Stranded with ferrule max	-
Dimensions	
PCB hole diameter	1.2 mm
Materials	
Thread insert, flange	Brass
Contact pin	Copper Alloy
Insulating Material	
Material	PA
Flammability class	UL 94 V-0
Temperatures	
Operating temperature	-40 °C (without mech. load) - 105 °C
Store temperature	-40 °C - 105 °C

Spacing 3.81 mm

Wave Soldering Process

Soldering temperature, recommended	260 °C
Peak soldering time, recommended	3-4 s

Reflow Process

Soldering temperature, recommended	217 - 245 °C
Peak soldering time, recommended	60 s

Colours

BLACK, RAL 9011

Colours according to RAL, there may be variations on colour due to production conditions.

Ratings

	c UL us			VDE
UseGroup	B	C	D	
Rated voltage	300 V	-	300 V	160 V
Rated current	10 A	-	10 A	10 A
Overvoltage category				III
Test voltage	1.60 kV	-	1.60 kV	2.5 kV
Pollution degree				3

Counterparts (Spacing 3.81 mm)

Terminal Block

AKZ1550	AKZ1700	AKZ1710	AKZ4551	AKZ4561

In combination of connectors with different admission data, the lower value is valid.

Tape on Reel

Number of Poles	Reel (RD/")	Width (R/mm)	Pitch (RP/mm)	Pieces (PCS)
2	13	56	16	200
3	13	56	16	200
4	13	56	16	200
5	13	56	16	200
6	13	56	16	200
7	13	56	16	200
8	13	56	16	200

Accessoires

Figure	Designation	Article Number
	Coding Star CS1-3.5/3.81-NATURAL-HT	Art.-Nr. 50000000022


PTR HARTMANN
A Phoenix Mecano Company

Spacing 3.81 mm

Order Data (Spacing 3.81 mm)

Number of Poles	Width (mm)	Article Designation	Article Number	PU
2	18.01	STLZ1550/2F-3.81-V-P2.6-BK-HT	51550026333R	200
3	21.82	STLZ1550/3F-3.81-V-P2.6-BK-HT	51550036333R	200
4	25.63	STLZ1550/4F-3.81-V-P2.6-BK-HT	51550046333R	200
5	29.44	STLZ1550/5F-3.81-V-P2.6-BK-HT	51550056333R	200
6	33.25	STLZ1550/6F-3.81-V-P2.6-BK-HT	51550066333R	200
7	37.06	STLZ1550/7F-3.81-V-P2.6-BK-HT	51550076333R	200
8	40.87	STLZ1550/8F-3.81-V-P2.6-BK-HT	51550086333R	200

Technical drawing



PTR HARTMANN
A Phoenix Mecano Company

