Technical Data // Series 1028/4 • 1028/5R

PTR HARTMANN
A Phoenix Mecano Company

ICT-Test Probe 100 mil / 2.54 mm

HIGHLIGHTS	
Metric design	
Collar Height 4.0 | 5.0 mm	
Contacting of assembled PCBs	
Large selection of tip styles	
MECHANICAL DATA	
Center	2.54 mm/100 mil
Full travel	5.30 mm
Working travel	4.00 mm
Pre-loaded spring force	0.30/ 0.40/ 0.50/ 0.70/ 1.00/ 1.00 N
Spring force at working travel	0.70/ 1.00/ 1.50/ 2.25/ 3.00/ 5.00 N
Temperature range	-30 °C - +120 °C
ELECTRICAL DATA	
Max. current rating	3.0...5.0 A
Typical continuity resistance	<= 25 mOhm
MATERIALS	
Barrel	Bronze/Brass, gold-plated
Spring	Spring Steel, Stainless Steel, gold-plated
Plunger	Steel, Plastic
Receptacle	Bronze, gold-plated
RECOMMENDED DIAMETER OF DRILL	
HP 2361.1 / EP CP 201 (trolitax)	1.99 mm
HGW 2372 (glass filled material)	2.00 mm
HIGH-TEMPERATURE APPLICATIONS	
Temperature range	-40 °C - +250 °C
Pre-loaded spring force	0.50/ 0.50/ 0.80 N
Spring force at working travel (order index E)	1.50/ 2.25/ 3.00 N

Technical Data // Series 1028/4 • 1028/5R

ICT-Test Probe 100 mil / 2.54 mm

TIP STYLE - DIAMETER - PLATING



A

1.50 Au
1.80 Ni




B

1.30 Rh




C

1.40 Au
1.80 Rh
2.00 Rh
2.50 Rh
3.50 Rh




CSM

1.00/2.00 Au/HTK




D

1.40 Au
2.00 Au



D1

0.65 Ni
0.80 Ni




EB

1.80 Au



F

1.30 Ni




G

1.30 Ni
1.50 Rh




H

1.30 Au




H

1.40 Au
1.80 Au



K

1.30 Au
1.75 Au/Ni




M6

2.00 Rh



Q

1.30 Au




Q

1.80 Au
2.00 Au




Q5

1.30 Ni




Q8

2.30 Ni



V


1.30 Ni



Technical Data // Series 1028/4 • 1028/5R

ICT-Test Probe 100 mil / 2.54 mm

Receptacles 1028/4 ? 1028/5R



HOW TO ORDER

1028	/5R	-	A	-	1.5 N	E	-	Au	-	1.5
1	2		3		4	5		6		7

1. Series 2. Collar Height 3. Tip Style
4. Spring Force 5. High Temperature 6. Tip Plating
7. Tip Diameter